



### **JUMBO FUEL TANKS**



# CONTAINERISED, SELF BUNDED (DOUBLE WALL)

Suitable for the Storage and Dispensing of Diesel, Lubricants, Kerosene and Petrol.



### **KEY FEATURES**

- Integrated Bunded Pump Bay and Tank Access
  Platform design providing access to the full tank
  functionality in one convenient location on the tank.
- Unique rounded rectangular tank profile maximises the storage capacity of the tank and provides the strength of a cylindrical design.
- Rounded roof profile that will not pool water / snow or sand.
- CSC plated as 10ft / 20ft / 40ft / 48ft Standard Container.
- Dispensing Equipment housed within a lockable bunded pump bay housing.
- Lockable Container Doors with option for Roller Door.
- Supplied with Interstitial Emergency Relief Vent that will relieve the gap between the two tanks in the event of a fire.
- DN80 Fill Point c/w Camlock Male Fitting / Dust Cap / Fire Safe Full Bore Ball Valve / Wafer Style Non Return Valve.
- DN80 Suction Outlet c/w Anti Syphon Valve and Two Piece Full Bore Fire Safe Ball Valve.
- DN80 Mechanical Overfill Valve + 12V Battery Operated Overfill Alarm.
- 2 x 600mm manways with integrated tank access ladder assembly.
- Fold out AS1657 designed and approved access ladder.
- Removable plate to allow the linking of multiple tanks in tank farm applications.
- Full under tank visibility allows for regular visual inspect of the tank base and prevents the base rusting by providing for unrestricted air flow under the tank.
- Paint Colour RAL9003 Signal White/ Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur Hi- Build 4520. Final Coat Hempathane Enamel 55100 Finished dry film thickness no less than 180 um.
- Supplied with all required statutory safety decals for your region of operation.









# **JUMBO FUEL TANKS**

| SIZE RANGE |          |                    |                |               |                |                |                        |                        |
|------------|----------|--------------------|----------------|---------------|----------------|----------------|------------------------|------------------------|
| CODE       | CAPACITY | SAFE FILL<br>LEVEL | LENGTH<br>(mm) | WIDTH<br>(mm) | HEIGHT<br>(mm) | WEIGHT<br>(kg) | CONTAINER<br>FOOTPRINT | INTEGRATED<br>PUMP BAY |
| XJ12       | 12,000L  | 10,100L            | 3,000          | 2,438         | 2,896          | 4,500          | 10FT High Cube         | Yes                    |
| XJ16       | 16,000L  | 15,000L            | 3,000          | 2,438         | 2,896          | 4,500          | 10FT High Cube         | No                     |
| XJ30       | 30,000L  | 26,500L            | 6,058          | 2,438         | 2,896          | 7,500          | 20FT High Cube         | Yes                    |
| XJ38       | 38,000L  | 33,500L            | 6,058          | 2,438         | 2,896          | 7,500          | 20FT High Cube         | No                     |
| XJ65       | 65,000L  | 62,300L            | 12,192         | 2,438         | 2,896          | 14,500         | 40FT High Cube         | Yes                    |
| XJ75       | 75,000L  | 69,000L            | 12,192         | 2,438         | 2,896          | 14,500         | 40FT High Cube         | No                     |

# **CERTIFICATIONS**

Certificate of Compliance #20120912-MH49221 for UL 142, ULC-\$601.



Decals manufactured to comply with AS1319 and AS2700.





