



927 LPM (245 GPM)

8.6 BAR (125 PSI)

76MM DIAPHRAGM PUMPS (3" AOD)



d or 3''
d or 3"
')
Dry, 8.6 m
1)
1)
9)

GENERAL SPECIFICATIONS

Max. Flow

Max. Head

Wetted Housing Aluminium

Centre Section Aluminium

Air Valve Aluminium

Non-Wetted Material Options Painted Aluminium

Air driven / pneumatic / diaphragm pumps are specifically designed for optimum performance and efficiency. They are driven by the well-known positive displacement pump technology.

Our 3" Air Operated Diaphragm pumps are metallic constructed and provide robust, reliable and high-performance pumping solution.

KEY FEATURES

- Aluminium Pump with ball valve design
- Designed to meet the performance requirements of even the most demanding pumping applications
- •Simple design with fewer wear parts
- Easier to diagnose & repair
- Lubrication free
- 1/2" BSP filter/regulator assembly
- 3" BSP thread or 3" Camlock inlets/outlets
- Safe for hazardous environments
- Marine orders 32 rated single lifting point (optional)
- Frame mounted pump (optional) at additional cost










76MM DIAPHRAGM PUMPS (3" AOD)

PUMP PERFORMANCE CURVE



PUMP DIMENSIONS

DIMENSIONS

ITEM	METRIC (mm)	STANDARD (inch)
A	514	20.2
В	61	2,4
C	411	16.2
D	416	16.4
E	758	29.8
F	816	32.1
G	70	2.8
Н	83	3.3
	399	15.7
K	49	1.9
L	213	8.4
M	425	16.7
N	722	28.4
P	710	28.0
R	319	12.5
5	307	12.1
T	257	10.1
U	281	11.1
V	16	0.6
W	71	2.8
X	74	2.9
Υ	308	12.1
Z	83	3.3
AA	305	12.0
AB	480	18.9
AC	16 DIA.	0.6 DIA

