



DIESEL GENERATOR 20kVA - KU



GENERATOR SPECIFICATIONS

SPECIFICATIONS	PRIME	
Voltage (V) all options	200, 380, 400, 415	
Frequency (Hz) / rpm	50/1500	60/1800
Dimensions (mm)	2070L x 800W x 1150H *	
Dry / operating mass	770 / 840 (wet)*	
Sound level *1 (dB/A)	90	
Pressure level *1 (db/A)	59	63
Class or rating	Continuous	

KEY FEATURES

- Genuine Japanese Mitsubishi engine
- Genuine Japanese Taiyo alternator
- Full IP56 / IP66 rated outlet kit optional
- Full MCB & RCD protection
- Earth leakage protection
- Fork pocketed bunded skid base
- Quick view control panel(with lighting)
- Remote start/stop controller (Optional)
- Lockable silenced super duty canopy
- Lockable fuel door
- Exhaust Rain Cap
- Certified Australian Standard Wiring
- Certified center lift point
- Certified tie down points
- Compliance plating
- Emergency stop
- Battery isolator
- External servicing drain points
- Fire Extinguisher
- Earth stake
- Operators manual
- 3 way fuel valve (optional)
- Site compliant fleet numbering (optional)
- Solar battery charging (optional)

ENGINE SPECIFICATION

Manufacturer and Model	KUBOTA V2403-K3A	
Cylinders	4 Cylinder	
Type - 4 Cycle water cooled	Swirl Chamber	
Total Displacement (L)	2.434	
Related Outputs PS (KW)	26 (19.1)	18.6 (13.7)
Fuel type and tank capacity	70L Diesel Fuel Oil	
Fuel consumption (L/hr) 50 / 75% load	3.0 / 4.0	2.2/3.0
Lubricating oil capacity (L)	9.5	
Cooling water capacity (L)	7.0	
Battery Capacity	80D26R(55) x1	

OUTPUT

PRIME 20kVA

ELECTRICAL SPECIFICATION

Power Factor	0.8
No. of phases	3-Phase, 4-Wire
Exciting method	Brushless (with A.V.R)

* Weights and dimensions include fork pocketed skid base

