



NPE U 190 AIR COMPRESSORS are compact, light-weight units with integrated features to maximise mobility and sound management. They are built for all demanding site conditions - with durable canopy configuration for easy access. Units are supplied in a secure, corrosion-free C3 rated canopy.



SPECIFICATIONS

Engine Make / Model	Kubota V 1505T – 4 Cylinder
Rated Output	32.5 KW / 44HP
Compressor type	Silenced, Single stage, oil-injected screw compressors
Displacement Air (CFM)	190cfm (3.5m ³ /hr)
Working pressure	100psi (7Bar)
Dimensions	2.1 m L x 1m W x 1.2m H
Weight	800Kg
Fuel tank capacity	62 Litres (8-10 L/hr consumption at full load)
Lifting	Marine Orders 32 rated single lifting point (optional)
Outlets	3 x 1" or 3/4" Minsup Type A (Isolation valves included)

SAFETY SHUTDOWNS

- ✓ Low engine oil pressure (Standard)
- ✓ High engine coolant temperature (Standard)
- ✓ High compressor oil temperature (Standard)
- ✓ Emergency stop (Standard)
- ✓ Battery, Starter isolator (Standard)
- ✓ Chalwyn-Air Intake Shutdown Diesel Engine Safety (Standard)
- ✓ Spark Arrestor (Standard)
- ✓ Certified Fire Extinguisher (Standard)
- ✓ PRV & Pressure vessel inspection report (Optional)